

---

## Offshore Support Vessels

### Notice to Shipbuilders, Shipowners, Masters, Ships' Officers and Shippers

---

1. All ships carrying hazardous and noxious liquid chemicals in bulk are subject to the Merchant Shipping (Control of Pollution by Noxious Liquid Substances in Bulk) Regulations 1987 as amended\* and the Merchant Shipping (Dangerous Goods and Marine Pollutants) Regulations 1990.† These Regulations give effect to Annex II to the International Convention for the Prevention of Pollution from Ships 1973, as amended by the Protocol of 78 thereto and as further amended and also to the International Convention for the Safety of Life at Sea 1974 as amended.

2. The International Maritime Organisation has agreed that in the case of offshore support vessels which carry limited amounts of certain hazardous and noxious liquid substances in bulk, full compliance with the Chemical or Gas Carrier Codes in order to satisfy the requirements of the Safety of Life at Sea (SOLAS) and the Prevention of Pollution from Ships (MARPOL) Conventions is unnecessary provided that:

- (i) the discharge of Category A, B and C noxious liquid substances, or ballast water, tank washings or residues or mixtures containing such substances must be to the offshore installation or to reception facilities in port; and
- (ii) the ships comply with the guidelines developed by the Organisation.

In adopting this approach, the Organisation considers that minimum risk is offered to the vessel, its crew and to the environment and the requirements for efficient stripping and underwater discharge arrangements in MARPOL 73/78 Annex II may therefore be waived.

3. The guidelines referred to in 2(ii) have been promulgated under IMO Resolution A673(16) and are entitled "Guidelines for the Transport and Handling of Limited Amounts of Hazardous and Noxious Liquid Substances in Bulk on Offshore Support Vessels".

4. The Secretary of State has agreed to issue a general exemption to offshore support vessels from the pertinent parts of those Regulations mentioned in paragraph 1 provided that the ships are surveyed, certificated and operated in accordance with the IMO Resolution. This general exemption and the "Guidelines" are attached as Annex 1 and Annex 2 to this Notice.

5. Application for survey and certification should be addressed in the first instance to the local Marine Office.

Department of Transport  
Marine Directorate  
London WC1V 6LP  
June 1991

© Crown copyright 1991

---

\* SI 1987/551 as amended by SI 1990/2604.

† SI 1990/2605.

**MERCHANT SHIPPING  
EXEMPTION  
POLLUTION  
SAFETY**

The Secretary of State in exercise of the powers conferred upon him by Regulation 27 of the Merchant Shipping (Control of Pollution by Noxious Liquid Substances in Bulk) Regulations 1987 as amended\*, and Regulation 1(6) of the Merchant Shipping (Dangerous Goods and Marine Pollutants) Regulations 1990† hereby exempts any offshore support vessel being a vessel used in carrying limited amounts of hazardous and noxious liquid substances in bulk for transfer to an offshore installation from compliance with:

Regulation 21 of the Merchant Shipping (Control of Pollution by Noxious Liquid Substances in Bulk) Regulations 1987 as amended; and

Regulation 16(2) of the Merchant Shipping (Dangerous Goods and Marine Pollutants) Regulations 1990;

provided that:

the vessel complies with the provisions of and operates in accordance with the International Maritime Organisation Resolution A673(16) entitled “Guidelines for the Transport and Handling of Limited Amounts of Hazardous and Noxious Liquid Substances in Bulk on Offshore Support Vessels”, and is so certified.

---

\* SI 1987/551 as amended by SI 1990/2604.

† SI 1990/2605.

THE ASSEMBLY,

RECALLING Article 15(j) of the Convention on the International Maritime Organisation concerning the functions of the Assembly in relation to regulations and guidelines concerning maritime safety and the prevention and control of marine pollution from ships,

NOTING the current practices of the offshore industry for servicing and resupplying mobile offshore drilling units and offshore platforms, including those employed in the search for and recovery of hydrocarbons from the sea-bed,

NOTING ALSO the continuing and increasing need for offshore support vessels to carry limited quantities of noxious and hazardous liquids in bulk in the normal course of their operations,

NOTING FURTHER that regulation 13(4) of Annex II to the International Convention for the Prevention of Pollution from Ships, 1973, as modified by the Protocol of 1978 relating thereto, calls for guidelines to be developed by the Organisation on the basis of which Administrations shall establish appropriate measures in respect of ships other than chemical tankers carrying noxious liquid substances of category A, B or C in bulk,

RECOGNISING that full application of the International Code for the Construction and Equipment of Ships Carrying Dangerous Chemicals in Bulk and the International Code for the Construction and Equipment of Ships Carrying Liquefied Gases in Bulk, in accordance with the International Convention for the Safety of Life at Sea, 1974, as amended and the International Convention for the Prevention of Pollution from Ships, 1973, as modified by the Protocol of 1978 relating thereto, to cover safety and pollution aspects is not necessary for offshore support vessels, having regard to the limited quantities of chemicals permitted to be carried, and to the modified requirements of the said instruments as contained in the Guidelines in the Annex to this resolution,

HAVING CONSIDERED the recommendations of the Maritime Safety Committee, at its fifty-seventh session, and the Marine Environment Protection Committee, at its twenty-sixth session,

1. ADOPTS the Guidelines for the Transport and Handling of Limited Amounts of Hazardous and Noxious Liquid Substances in Bulk on Offshore Support Vessels, the text of which is contained in the Annex to this resolution;
2. INVITES all Governments concerned:
  - (a) to take appropriate steps to give effect to the Guidelines as early as possible;
  - (b) to inform the Organisation on measures taken to apply the Guidelines;
3. AUTHORISES the Maritime Safety Committee and the Marine Environment Protection Committee to amend the Guidelines as may be necessary.

## ANNEX

### GUIDELINES FOR THE TRANSPORT AND HANDLING OF LIMITED AMOUNTS OF HAZARDOUS AND NOXIOUS LIQUID SUBSTANCES IN BULK ON OFFSHORE SUPPORT VESSELS

#### CONTENTS

	Page
Preamble	5
Chapter 1—General	6
1.1 Application	6
1.2 Scope	6
1.3 Definitions	7
1.4 Equivalents	7
1.5 Survey and certification	8
Chapter 2—Stability and cargo tank location	8
2.1 Stability	8
2.2 Cargo tank location	8
Chapter 3—Ship design	8
3.1 Cargo segregation	8
3.2 Accommodation, service and machinery spaces and control stations	9
3.3 Access to spaces in the cargo area	9
3.4 Cargo tank construction	9
3.5 Materials of construction	10
3.6 Cargo tank vent systems	10
3.7 Cargo transfer	10
3.8 Electrical installations	10
3.9 Fire-fighting requirements	10
3.10 Acid spill protection	11
3.11 Ventilation of spaces in the cargo area	12
3.12 Vapour detection	12
3.13 Special requirements-general	12
3.14 Special requirements for the carriage of liquefied gases	12
3.15 Gauging and level detection	12
3.16 Emergency remote shutdown	12
Chapter 4—Pollution requirements	12
Chapter 5—Personnel protection	13
5.1 Decontamination showers and eyewashes	13
5.2 Protective and safety equipment	13
Chapter 6—Operational requirements	13
Chapter 7—Applicability of the Guidelines to existing offshore support vessels	13
Appendix 1—Table of permitted cargoes	14
Appendix 2—Model form of Certificate of Fitness	15

## PREAMBLE

1. These Guidelines have been developed for the design, construction and operation of offshore support vessels which transport limited amounts of hazardous and noxious liquid substances in bulk for the servicing and re-supplying of offshore platforms, mobile offshore drilling units and other offshore installations, including those employed in the search for, and recovery of, hydrocarbons from the sea-bed.
2. They have been developed in accordance with the provisions set forth in regulation 13(4) of Annex II to MARPOL 73/78 and in recognition of the need for standards for offshore support vessels which provide an alternative to the International Code for the Construction and Equipment of Ships Carrying Dangerous Chemicals in Bulk and the International Code for the Construction and Equipment of Ships Carrying Liquefied Gases in Bulk.
3. The Guidelines are intended to permit limited quantities of hazardous and noxious liquid substances to be transported in bulk in offshore support vessels with minimum risk to the vessel, its crew and the environment.
4. The basic philosophy of the Guidelines is to apply standards contained in the International Code for the Construction and Equipment of Ships Carrying Dangerous Chemicals in Bulk and the International Code for the Construction and Equipment of Ships Carrying Liquefied Gases in Bulk.
5. The Guidelines for the Design and Construction of Offshore Supply Vessels (resolution A.469 (XII)) adopted on 19 November 1981 are also applicable to offshore support vessels subject to these Guidelines.
6. It is recognised that the technology of the Offshore industry is complex and subject to continued evolution as is evidenced by the growing need for specialised vessels such as well-stimulation vessels. To meet the needs of the industry the Guidelines should not remain static. Therefore the International Maritime Organisation will periodically review the contents, taking into account both experience and technical development. Amendments to the Guidelines involving requirements for new cargoes will be circulated periodically as new cargoes are proposed for carriage and the requirements are developed.

## CHAPTER I—GENERAL

### 1.1 Application

1.1.1. The Guidelines apply to offshore support vessels, regardless of size or voyage, which, while not constructed or adapted primarily to carry bulk cargoes subject to these Guidelines, carry, in limited quantities, the substances identified in 1.2.2. The Guidelines apply when such cargoes are carried.

1.1.2. For an offshore support vessel the keel of which is laid or which is at a similar stage of construction on or after 1 January 1991, the requirements in Chapters 1 to 6 apply in full. For an offshore support vessel the keel of which was laid or which was at a similar stage of construction prior to 1 January 1991, the Guidelines apply as indicated in Chapter 7.

1.1.3. A vessel irrespective of the date of construction, which is converted for the carriage of bulk liquids subject to these Guidelines on or after the date specified in 1.1.2, should be treated as a vessel constructed on the date on which such conversion commences. An existing offshore support vessel which transports a cargo subject to these Guidelines and undergoes modification for the transport of additional cargoes falling under these Guidelines should not be considered as a vessel which has undergone a conversion.

1.1.4 For the purpose of these Guidelines, "limited quantities" means that the aggregate quantity of bulk liquids identified in 1.2.2 that is carried is any amount not exceeding a maximum which is the lesser of 800 m<sup>3</sup> or a volume in cubic metres equal to 40 per cent of the vessel's deadweight calculated at a cargo density of 1.0. For ships referred to in 1.3.4.2, such as well-stimulation vessels, the Administration may permit carriage of more than the maximum amount specified above.

1.1.5 For other ships, the Administration may permit carriage of more than the relevant maximum amount specified above, provided that the survival capability requirements of Chapter 2 of the International Bulk Chemical Code or the International Gas Carrier Code are complied with.

1.1.6 The Guidelines apply only in the case of bulk carriage involving transfer of the cargo to or from its containment which forms part of the vessel or remains on board.

1.1.7 Carriage and handling of dangerous goods and marine pollutants in packaged form should be in accordance with the recommendations of the International Maritime Dangerous Goods Code.

1.1.8 These Guidelines apply in addition to the Guidelines for the Design and Construction of

Offshore Supply Vessels (resolution A.469(XII)). Where the present Guidelines set forth alternative safety standards to those contained in resolution A.469(XII), the standards in the present Guidelines should be followed.

### 1.2 Scope

1.2.1 The provisions of the Guidelines have been developed so that limited quantities of cargoes regulated under the Guidelines may be carried in bulk with minimum risk to the offshore support vessel, its crew, and to the environment.

1.2.2 Products which may be carried subject to the Guidelines are:

- .1 those hazardous and noxious liquids listed in Appendix 1 and those other products which may be assigned to Appendix 1 based on the following criteria:
  - .1.1 products which for safety reasons may be assigned for carriage on a type 3 ship as defined by the International Bulk Chemical Code and which are not required to meet the requirements for toxic products in section 15.12 of that Code,
  - .1.2 category A, B and C noxious liquid substances which would be permitted for carriage on a type 3 ship;
- .2 flammable liquids.

1.2.3 Additives which are considered to fall outside the scope of products in 1.2.2 may be carried in limited amounts in accordance with requirements acceptable to the Administration. The aggregate amount of such additives which may be transported should not exceed 10 per cent of the vessel's maximum authorised quantity of products subject to these Guidelines. An individual tank should contain not more than 10m<sup>3</sup> of these additives. The discharge of these additives into the sea from offshore support vessels is prohibited.

1.2.4 Carriage of products not listed in Appendix 1 should be undertaken only in accordance with suitable preliminary carriage conditions prescribed by the Administration, having regard to the criteria for hazard evaluation of bulk chemicals as approved by the Organisation and the limitation referred to in 1.2.2. The Organisation should be notified of the preliminary evaluation and conditions so that the hazardous material may be considered for inclusion in Appendix 1.

### 1.3 Definitions

Unless expressly provided otherwise, the definitions contained in Chapters 1 and 4 of the International Bulk Chemical Code apply.

1.3.1 *Cargo area* is that part of the offshore support vessel where cargo and cargo vapours are likely to be present and includes cargo tanks, cargo pump-rooms, hold spaces in which independent tanks are located, cofferdams surrounding integral tanks and the following deck areas:

- 1 within 3 metres of a cargo tank installed on deck;
- 2 within 3 metres of a cargo tank outlet in case of independent tanks installed below deck;
- 3 within 3 metres of a cargo tank outlet in case of integral tanks installed below deck and separated from the weather deck by a cofferdam;
- 4 the deck area above an integral tank without an overlaying cofferdam plus the deck area extending transversely and longitudinally for a distance of 3 metres beyond each side of the tank;
- 5 within 3 metres of any cargo liquid or vapour pipe, flange, cargo valve, gas or vapour outlet, or entrance or ventilation opening to a cargo pump-room.

1.3.2 *Deadweight* means the difference in metric tons between the displacement of an offshore support vessel in water of a density of 1.025 at the load waterline corresponding to the assigned summer freeboard and the lightweight of the ship.

1.3.3 *Lightweight* means the displacement of an offshore support vessel in metric tons without cargo, fuel, lubricating oil, ballast water, fresh water and feed water in tanks, consumable stores, and passengers and crew and their effects.

1.3.4 *Offshore support vessels* are:

- 1 vessels which are primarily engaged in the transport of stores, materials and equipment to and from mobile offshore drilling units, fixed and floating platforms and other similar offshore installations; or
- 2 vessels, including well-stimulation vessels, but excluding mobile offshore drilling units, derrick barges, pipelaying barges and floating accommodation units, which are otherwise primarily engaged in supporting the work of offshore installations.

1.3.5 *Hazardous substance* is any substance either listed in Chapter 17 of the International Bulk Chemical Code or having a hazard more severe than one of the minimum hazard criteria given in criteria for hazard evaluation of bulk chemicals as approved by the Organisation.

1.3.6 *Noxious liquid substance* is any substance listed in Appendix II to Annex II to MARPOL 73/78 as amended, as a category A substance, a category B substance, a category C substance, a category D substance, and any substance provisionally listed in such categories.

1.3.7 *Pollution hazard only substance* means a substance having an entry only of "P" in column d in Chapter 17 of the International Bulk Chemical Code.

1.3.8 *Safety hazard substance* means a substance having an entry of "S" or "S/P" in column d in Chapter 17 of the International Bulk Chemical Code.

1.3.9 *Flammable liquid* is any liquid having a flash-point not exceeding 60°C (closed cup test).

1.3.10 *International Bulk Chemical Code* means the International Code for the Construction and Equipment of Ships Carrying Dangerous Chemicals in Bulk (resolutions MSC.4(48) and MEPC.19(22)), (as amended).

1.3.11 *International Gas Carrier Code* means the International Code for the Construction and Equipment of Ships Carrying Liquefied Gases in Bulk (resolution MSC.5(48)), (as amended).

1.3.12 *MARPOL73/78* means the International Convention for the Prevention of Pollution from Ships, 1973, as modified by the Protocol of 1978 relating thereto.

1.3.13 *1974 SOLAS Convention, as amended*, means the International Convention for the Safety of Life at Sea, 1974, as amended.

1.3.14 *Administration*, in these Guidelines, means the Marine Directorate of the Department of Transport.

1.3.15 *Organisation*, in these Guidelines, means the International Maritime Organisation.

### 1.4 Equivalents

1.4.1 When these Guidelines require that a particular fitting material, appliance, apparatus, item of equipment or type thereof should be fitted or carried in an offshore support vessel, or that any particular provision should be made, or any procedure or arrangement

should be complied with, the Administration may allow any other fitting, material, appliance, apparatus, item of equipment or type thereof to be fitted or carried, or any other provision, procedure or arrangement to be made in that ship, if it is satisfied by trial thereof or otherwise that such fitting, material, appliance, apparatus, item of equipment or type thereof or that any particular provision, procedure or arrangement is at least as effective as that required by the Guidelines. However, the Administration may not allow operational methods or procedures to be made an alternative to a particular fitting, material, appliance, apparatus item of equipment, or type thereof, which are prescribed by these Guidelines, unless such substitution is specifically allowed by these Guidelines.

1.4.2 When the Administration so allows any fitting, material, appliance, apparatus, item of equipment, or type thereof, or provision, procedure, or arrangement, or novel design or application to be substituted thereafter, it should communicate to the Organisation the particulars thereof together with a report on the evidence submitted so that the Organisation may circulate the same to other Contracting Governments to the 1974 SOLAS Convention, as amended, and Parties to MARPOL 73/78, for the information of their officers.

### 1.5 Survey and Certification

1.5.1 Following a satisfactory initial survey of an offshore support vessel, the Administration or its duly

authorised organisation should issue a certificate, the model form of which is set out in Appendix 2, suitably endorsed to certify compliance with the provisions of the Guidelines. The certificate should indicate the cargoes regulated by these Guidelines that the vessel is permitted to carry with any relevant carriage conditions and should have a period of validity not to exceed five years.

1.5.2 The certificate issued under these Guidelines should have the same force and receive the same recognition as the certificate issued under regulation 11 of Annex II of MARPOL 73/78 and regulations VII/10 and VII/13 of the 1974 SOLAS Convention, as amended.

1.5.3 When the vessel is constructed to carry substances having only a marine pollution hazard, the International Pollution Prevention Certificate for the Carriage of Noxious Liquid Substances in Bulk required under MARPOL 73/78, Annex II may be suitably endorsed and serve the purpose of 1.5.1.

1.5.4 The validities of the certificates referred to in 1.5.1 and 1.5.3 should be subject to the periodical, intermediate, annual and additional surveys required by the International Bulk Chemical Code, the International Gas Carrier Code and MARPOL 73/78, Annex II.

## CHAPTER 2—STABILITY AND CARGO TANK LOCATION

### 2.1 Stability

2.1.1 Offshore support vessels built in accordance with these Guidelines should be designed to meet the requirements for intact stability and for subdivision and damage stability contained in the Guidelines for the Design and Construction of Offshore Supply Vessels (resolution A.469(XII)).

2.1.2 Well-stimulation vessels which are permitted to carry more than the maximum amounts specified in 1.1.4 should be designed to meet the requirements for intact stability and for subdivision and damage

stability contained in the Guidelines for the Design and Construction of Offshore Supply Vessels, but with the damage given in 3.2.1 of those Guidelines occurring anywhere in the ship's length at any transverse watertight bulkhead.

### 2.2 Cargo Tank Location

Cargo tanks containing products subject to the provisions of the Guidelines should be located at least 760 mm measured inboard from the side of the vessel perpendicular to the centreline at the level of the summer load waterline.

## CHAPTER 3—SHIP DESIGN

### 3.1 Cargo Segregation

3.1.1 Tanks containing cargo or residues of cargo subject to the provisions of the Guidelines should be segregated from machinery spaces, propeller shaft tunnels (if fitted), dry cargo spaces, accommodation and service spaces and from drinking water and stores for

human consumption, by means of a cofferdam, void space, cargo pump-room, empty tank, oil fuel tank, or other similar space. On-deck stowage of independent tanks, or installing independent tanks in otherwise empty hold spaces, should be considered as satisfying this requirement.

3.1.2 Cargoes which react in a hazardous manner with other cargoes or oil fuels should:

- .1 be segregated from such other cargoes or oil fuels by means of a cofferdam, void space, cargo pump-room, pump-room, empty tank, or tank containing a mutually compatible cargo;
- .2 have separate pumping and piping systems which should not pass through other cargo tanks containing such cargoes, unless encased in a tunnel; and
- .3 have separate tank venting systems.

3.1.3 Cargo piping should not pass through any accommodation, service or machinery space other than cargo pump-rooms or pump-rooms.

3.1.4 Pumps, ballast lines, vent lines and other similar equipment serving permanent ballast tanks should be independent of similar equipment serving cargo tanks.

3.1.5 Bilge pumping arrangements for cargo pump-rooms, or for hold spaces in which independent cargo tanks are installed should be situated entirely within the cargo area.

#### *Segregation Requirements for Integral Tanks*

3.1.6 Where not bounded by bottom shell plating, fuel oil tanks, a cargo pump-room or a pump-room, the cargo tanks should be surrounded by cofferdams. Tanks for other purposes (except fresh water and lubricating oils) may be accepted as cofferdams for these tanks.

3.1.7 For access to all spaces, the minimum spacing between cargo tank boundaries and adjacent ship's structures should be 600 mm.

3.1.8 Cargo tanks may extend to the deck plating, provided dry cargo is not handled in that area. Where dry cargo is handled on the deck area above a cargo tank, the cargo tank may not extend to the deck plating unless a continuous, permanent deck sheathing of wood or other suitable material of appropriate thickness and construction is fitted to the satisfaction of the Administration.

3.1.9 Cargoes subject to the Guidelines should not be carried in either the fore or aft peak tanks.

3.1.10 For pollution hazard only substances having a flashpoint exceeding 60°C (closed cup test) the Administration may waive the arrangements referred to in 3.1.1 and 3.1.3 provided that the segregation requirements for accommodation spaces, drinking water and stores for human consumption are observed. Additionally, 3.1.6 and 3.1.7 need not be applied.

### **3.2 Accommodation, Service and Machinery Spaces and Control Stations**

3.2.1 Accommodation or service spaces, or control stations should not be located within the cargo area.

3.2.2 Unless they are spaced at least 7 metres away from the cargo area containing flammable products, entrances, air inlets and openings to accommodation, service and machinery spaces and control stations should not face the cargo area. Doors to spaces not having access to accommodation, service and machinery spaces and control stations, such as cargo control stations and store-rooms, may be permitted by the Administration within the 7 metre zone specified above, provided the boundaries of the spaces are insulated to A-60 standard. When arranged within the 7 metre zone specified above, windows and sidescuttles facing the cargo area should be of a fixed type. Such sidescuttles in the first tier on the main deck should be fitted with inside covers of steel or equivalent material.

3.2.3 In order to guard against the danger of hazardous vapours, due consideration should be given to the location of air intakes and openings into accommodation, service and machinery spaces and control stations in relation to cargo piping and cargo vent systems.

3.2.4 For pollution hazard only substances having a flashpoint exceeding 60°C, the arrangements referred to in 3.2.1 to 3.2.3 may be waived.

### **3.3 Access to spaces in the cargo area**

Access to spaces within the cargo area should meet the requirements of 3.4 of the International Bulk Chemical Code.

### **3.4 Cargo tank construction**

3.4.1 Cargo tanks should be at least of the type required for the cargo by the International Bulk Chemical Code or the International Gas Carrier Code, as applicable.

3.4.2 Portable tanks meeting the requirements of section 13 of the General Introduction to the International Maritime Dangerous Goods Code for the cargo concerned or other portable tanks specifically approved by the Administration may be used, provided that they are properly located and secured to the vessel.

3.4.3 Except for the tank connections to cargo pump-rooms, all tank openings and connections to the tank should terminate above the weather deck and should be located in the tops of the tanks. Where cofferdams are provided over integral tanks, small trunks may be used to penetrate the cofferdam.

3.4.4 The greater of the following design pressures (gauge) should be used for determining scantlings of independent pressure tanks:

- .1 0.7 bar;
- .2 the vapour pressure of the cargo at 45°C;
- .3 the vapour pressure of the cargo at 15°C above the temperature at which it is normally carried; or
- .4 the pressure which occurs in the tank during the loading or unloading;

The design of the tanks should comply with standards acceptable to the Administration taking into account the carriage temperature and relative density of cargo. Due consideration should also be given to dynamic forces and any vacuum pressure to which the tanks may be subjected.

3.4.5 Integral and independent gravity tanks should be constructed and tested according to standards of the Administration taking into account the carriage temperature and relative density of cargo.

3.4.6 For pollution hazard only substances having a flashpoint exceeding 60°C, the requirements of 3.4.3 need not be applied.

### 3.5 Materials of Construction

Materials of construction for tanks, piping, fittings and pumps should be in accordance with Chapter 6 of the International Bulk Chemical Code, or Chapter 6 of the International Gas Carrier Code, as applicable.

### 3.6 Cargo Tank Vent Systems

3.6.1 Independent pressure tanks should be fitted with pressure relief devices that are so designed as to direct the discharge away from personnel and that have a set pressure and capacity which is in accordance with standards acceptable to the administration taking into account the design pressure referred to in 3.4.4.

3.6.2 Cargo tank vent systems of integral or independent gravity tanks should meet the requirements of the International Bulk Chemical Code, except that the height specified in 8.2.2 of the Code may be reduced to 2 metres.

3.6.3 The location of cargo tank vent outlets for independent pressure tanks and for cargo tanks used to carry pollution hazard only substances with a flashpoint exceeding 60°C (closed cup test) should be to the satisfaction of the Administration.

3.6.4 Cargo tank vent systems of portable tanks allowed under 3.4.2 should be to the satisfaction of the Administration, taking into account the requirements of 3.6.

### 3.7 Cargo Transfer

3.7.1 The cargo transfer system should comply with the requirements of Chapter 5 of the International Bulk Chemical Code or Chapter 5 of the International Gas Carrier Code when considered applicable and practical by the Administration, taking into account existing industry standards and practices.

3.7.2 The remote shutdown devices for all cargo pumps and similar equipment, required by 5.6.1.3 of the International Bulk Chemical Code, should be capable of being activated from a dedicated cargo control location which is manned at the time of cargo transfer and from at least one other location outside the cargo area and at a safe distance from it.

### 3.8 Electrical Installations

Electrical installations should meet the requirements of Chapter 10 of the International Bulk Chemical Code.

### 3.9 Fire-fighting Requirements

3.9.1 For the carriage of flammable liquids identified in Appendix 1, the requirements for tankers in Chapter II-2 of the 1974 SOLAS Convention, as amended, should apply to vessels covered by the Guidelines, irrespective of tonnage, including vessels of less than 500 tons gross tonnage, except that:

- .1 regulations 60,61,62 and 63 should not be applied;
- .2 regulation 56.1 (i.e. positioning of machinery spaces aft of cargo tanks, slop tanks, cargo pump-rooms and cofferdams), regulation 56.2 (i.e. the requirements for location of the main cargo control station), regulations 56.4 and 56.8 need not be applied. Additionally, regulation 56.7 need not be applied provided that the exterior boundaries of superstructures and deckhouses enclosing accommodation and including any overhanging decks which support such accommodation are spaced at least 7 metres away from the cargo area. The insulation of such boundaries should however be to the satisfaction of the Administration;
- .3 with regard to regulation 57.1, the Administration may permit use of a method other than IC as defined in regulation 42.5.1 where considered appropriate;

- .4 the requirements of regulation 44 may be applied in lieu of those in regulation 58, where considered appropriate by the Administration;
- .5 the provisions of regulation 59 need be applied only where considered appropriate by the Administration, taking into account the requirement in 3.6.2 of the Guidelines that cargo tank vent systems should meet the relevant requirements of the International Bulk Chemical Code;
- .6 regulation 4, as applicable to cargo ships, and regulation 7 should apply as they would apply to tankers of 2,000 tons gross tonnage and over;
- .7 the provisions of 3.9.2.3 should be applied in lieu of regulation 61; and
- .8 the provisions of 3.9.2.5 should be applied in lieu of regulation 63.

3.9.2 The following provisions also apply for the carriage of flammable liquids identified in Appendix 1:

- .1 During cargo transfer, water pressure should be maintained on the fire main system.
- .2 Fire hoses, fitted with approved dual-purpose nozzles (i.e. spray/jet type with a shutoff), should be attached to each fire hydrant in the vicinity of the flammable liquid to be carried.
- .3 Either a fixed deck foam system or a fixed fire-extinguishing system of the dry chemical type complying with the following should be provided:
  - .3.1 the system should be located to protect the deck within the cargo area;
  - .3.2 the system should be capable of covering the deck within the cargo area without being moved;
  - .3.3 when a fixed deck foam system is provided, it should comply with the requirements of 11.3.3 to 11.3.12 of the International Bulk Chemical Code. Only foam suitable for the products carried should be used.
  - .3.4 Administrations may approve a fixed fire-extinguishing system provided that:
    - .3.4.1 on a deck area of 45 m<sup>2</sup> or less, there are two or more dry chemical extinguishers whose total capacity is not less than 135 kg;

- .3.4.2 on a deck area of more than 45 m<sup>2</sup>, there are three or more dry chemical extinguishers whose total capacity of extinguishing agent is not less than:

$$C=3A \text{ kg}$$

where A is the deck area (in square metres);

- .3.4.3 the minimum rate of supply of the extinguishing agent is not less than 3 kg/min per square metre.
- .4 An alternative to the systems required in 3.9.2.3 above may be approved in accordance with the procedures contained in regulation II-2/22 of the 1974 SOLAS Convention, as amended.
- .5 The cargo pump-room where flammable liquids are handled should be provided with a fixed fire-extinguishing system in accordance with 11.2 of the International Bulk Chemical Code.

3.9.3 For vessels which carry only liquids identified as non-flammable in Appendix 1, the fire-fighting requirements should be to the satisfaction of the Administration.

### 3.10 Acid Spill Protection

3.10.1 Floors or decks under acid storage tanks and pumps and piping for acid should have a lining or coating of corrosion-resistant material extending up to a minimum height of 500 mm on the bounding bulkheads or coamings. Hatches or other openings in such floors or decks should be raised to a minimum height of 500 mm; however, where the Administration determines that this height is not practicable a lesser height may be required.

3.10.2 Flanges or other detachable pipe connections should be covered by spray shields.

3.10.3 Portable shields for covering the flanges of the loading manifold should be provided. Drip trays of corrosion-resistant material should be provided under loading manifolds for acids.

3.10.4 Spaces for acid storage tanks and acid pumping and piping should be provided with drainage arrangements of corrosion-resistant materials.

3.10.5 Deck spills should be kept away from accommodation and service areas by means of a permanent coaming of suitable height and extension.

### 3.11 Ventilation of Spaces in the Cargo Area

The requirements of Chapter 12 of the International Bulk Chemical Code apply. The Administration may, however, grant relaxations concerning the distances required in 12.1.5 of the Code.

### 3.12 Vapour Detection

3.12.1 Vapour detection for the cargoes carried should be provided in accordance with the requirements contained in the International Bulk Chemical Code.

3.12.2 Enclosed and semi-enclosed spaces containing installations for acid should be fitted with fixed vapour detection and alarm systems which provide visual and audible indication. The vapour detection systems should be capable of detecting hydrogen except that, in the case where only hydrochloric acid is carried, a hydrogen chloride vapour detection system should be provided.

3.12.3 At least two portable instruments for detecting flammable vapour concentrations should be provided when cargoes subject to these Guidelines with a flashpoint not exceeding 60°C (closed cup test) are carried.

3.12.4 At least two portable instruments suitable for measuring the concentration of oxygen in atmospheric air should be provided.

### 3.13 Special Requirements—General

The special requirements for the cargo as referred to in Chapter 17 of the International Bulk Chemical Code or Chapter 19 of the International Gas Carrier Code are applicable; however, the requirement in 15.19.6 of the International Bulk Chemical Code for a visual and audible high-level alarm may be waived by the Administration taking into account the cargo carriage arrangements and cargo loading procedures.

### 3.14 Special Requirements for the Carriage of Liquefied Gases

3.14.1 Each enclosed space used for handling or storage of a liquefied gas should be fitted with a

sensor continuously monitoring the oxygen content of the space and an alarm indicating low oxygen concentration. For semi-enclosed spaces portable equipment may also be acceptable.

3.14.2 Drip trays resistant to cryogenic temperatures should be provided at manifolds transferring liquefied gases or at other flanged connections in the liquefied gas system.

3.14.3 For the carriage of liquid nitrogen the requirements of 17.19 of the International Gas Carrier Code should apply.

3.14.4 The construction of cargo tanks and cargo piping systems for liquefied nitrogen and liquid carbon dioxide should be to the satisfaction of the Administration.

3.14.5 Emergency shutoff valves should be provided in liquid outlet lines from each liquefied gas tank. The controls for the emergency shutoff valves should meet the requirements given in 3.7.2 for remote shutdown devices.

### 3.15 Gauging and Level Detection

Each cargo tank should have a level gauging system acceptable to the Administration. As a minimum the system should meet relevant requirements of the International Bulk Chemical Code and the International Gas Carrier Code. The systems for process tanks on board well-stimulation vessels should be to the satisfaction of the Administration.

### 3.16 Emergency Remote Shutdown

In the case of transfer operations involving pressures in excess of 50 bar gauge, arrangements for emergency depressurising and disconnection of the transfer hose should be provided. The controls for activating emergency depressurising and disconnection of the transfer hose should meet the requirements given in 3.7.2 for remote shutdown devices.

## CHAPTER 4—POLLUTION REQUIREMENTS

4.1 Each ship certified to carry a noxious liquid substance should be provided with a Cargo Record Book and a Procedures and Arrangements Manual developed for the ship in accordance with the provi-

sions of the Standards for Procedures and Arrangements for the Discharge of Noxious liquid Substances (resolution MEPC.18(22) and approved by the Administration.

4.2 Discharge into the sea of category A, B and C noxious liquid substances or ballast water, tank washings, or other residues or mixtures containing such substances, is prohibited. Any discharges of residues and mixtures containing noxious liquid substances should be to reception facilities in port. As a consequence of this prohibition, the Administration may waive the requirements for efficient stripping and underwater discharge arrangements in MARPOL 73/78, Annex II.

4.3 Residues of category D substances, tank washings, other mixtures or ballast water containing such substances may be discharged into the sea provided that the discharge is in accordance with the relevant conditions as required under MARPOL 73/78, Annex II.

4.4 In the case of cargoes regulated by MARPOL 73/78, Annex I, the requirements of that Annex should apply as appropriate.

## **CHAPTER 5—PERSONNEL PROTECTION**

### **5.1 Decontamination Showers and Eyewashes**

Except in the case of pollution hazard only substances, a suitably marked decontamination shower and eyewash should be available on deck in a convenient location. The shower and eyewash should be operable in all ambient conditions.

### **5.2 Protective and Safety Equipment**

Protective and safety equipment should be kept on board in suitable locations as required by Chapter 14 of the International Bulk Chemical Code or the International Gas Carrier Code for products to be carried.

## **CHAPTER 6—OPERATIONAL REQUIREMENTS**

6.1 Deck cargo and products covered by these Guidelines should not be loaded or unloaded simultaneously.

6.2 Only personnel engaged in the transfer of cargo covered by those Guidelines should be permitted to be in the cargo area and the adjacent open main deck during loading or unloading operations.

## **CHAPTER 7—APPLICABILITY OF THE GUIDELINES TO EXISTING OFFSHORE SUPPORT VESSELS**

The provisions of the Guidelines should apply to offshore support vessels the keels of which are laid or which are at a similar stage of construction before the date specified in 1.1.2 as follows.

Chemical Code and the International Gas Carrier Code need not be applied to vessels referred to in 1.3.4.2.

7.1 The provisions of Chapter 1 of these Guidelines should apply except that, with reference to 1.1.4:

- .1 larger quantities of bulk liquids may be permitted by the Administration on an individual vessel basis;
- .2 the survival capability requirements of Chapter 2 of the International Bulk

7.2 The provisions of Chapters 2 and 3 of the Guidelines should be applied where deemed reasonable and practicable by the Administration taking full account of the present arrangements and equipment of the vessel. Recognising that existing vessels may not meet many of the requirements of these chapters, relaxations may be granted.

7.3 The provisions of Chapters 4 to 6 of the Guidelines should be applied.

**APPENDIX 1**

**TABLE OF PERMITTED CARGOES**

	Annex II, MARPOL 73/78 pollution category	Flammability
Acetic acid (aqueous solution)	C(D)	Yes
Fornic acid (aqueous solution)	D	Yes
Hydrochloric acid	D	No
Hydrochloric-hydrofluoric mixtures containing 3% or less hydrofluoric acid	D	No
Sulphuric acid	C	No
Toluene	C	Yes
Xylene	C	Yes
Zinc bromide brine	(A)	No
Liquid carbon dioxide	N/A	No
Liquid nitrogen	N/A	No

**APPENDIX 2**

**MODEL FORM OF CERTIFICATE OF FITNESS**

**CERTIFICATE OF FITNESS**

**(Official seal)**

**Issued under the provisions of the**

**GUIDELINES FOR THE TRANSPORT AND HANDLING OF LIMITED AMOUNTS OF  
HAZARDOUS AND NOXIOUS LIQUID SUBSTANCES IN BULK ON OFFSHORE  
SUPPORT VESSELS  
(resolution A.673(16))**

under the authority of the Government of

.....  
(full official designation of country)

by .....  
(full official designation of the competent person  
or organisation recognised by the Administration)

Name of vessel	Distinctive number or letters	Port of registry	Gross tonnage	Deadweight

Date on which keel was laid or on which the vessel was at a similar stage of construction or (in the case of a converted vessel) date on which conversion for the carriage of bulk liquids subject to these Guidelines was commenced:

.....

\_\_\_\_\_

The Certificate should be drawn up in the official language of the issuing country. If the language used is neither English nor French, the text should include a translation into one of these languages.

The vessel also complies fully with the following amendments to the Guidelines:

.....  
.....

The vessel is exempted from compliance with the following provisions of the Guidelines:

.....  
.....

THIS IS TO CERTIFY:

1. .1 That the vessel has been surveyed in accordance with the provisions of 1.5 of the Guidelines;  
 .2 that the survey showed that the construction and equipment of the vessel  
 \*.2.1 complied with the relevant provisions of the Guidelines applicable to “new” vessels,  
 \*.2.2 complied with the provisions of the Guidelines in respect of “existing” vessels;
2. That the vessel has been provided with a manual in accordance with the standards for procedures and arrangements as called for by regulations 5, 5A and 8 of Annex II of MARPOL 73/78, and that the arrangements and equipment of the vessel prescribed in the manual are in all respects satisfactory and comply with the applicable requirements of the said Standards;
3. That the vessel is suitable for the carriage in bulk of the following products, provided that all relevant operational provisions of the Guidelines are observed:

Products <sup>1,2</sup>	Conditions of carriage (tank numbers, etc.)

NB: Continued on attachment 1, additional signed and dated sheets.  
 Tank numbers referred to in this list are identified on attachment 2, signed and dated tank plan.

4. That, in accordance with \*1.4 of the Guidelines and \*2.8.2 of the IBC Code, the provisions of the Guidelines and the Code are modified in respect of the vessel in the following manner:  
 .....

5. That the vessel must be loaded:
  - \*.1 in accordance with the loading conditions provided in the approved loading manual, stamped and dated ..... and signed by a responsible officer of the Administration, or of an organisation recognised by the Administration;
  - \*.2 in accordance with the loading limitations appended to this Certificate.

Where it is required to load the vessel other than in accordance with the above instructions, then the necessary calculations to justify the proposed loading conditions should be communicated to the certifying Administration who may authorise in writing the adoption of the proposed loading condition.†

This certificate is valid until .....  
 subject to surveys in accordance with 1.5 of the Guidelines.

Issued at ..... 19....  
 (place of issue of Certificate)

The undersigned declares that he is duly authorised by the said Government to issue this Certificate.

.....  
 (signature of official issuing the Certificate  
 and/or seal of issuing authority)

\* Delete as appropriate,  
 † Instead of being incorporated in the Certificate, this text may be appended to the Certificate if duly signed and stamped.

Notes on completion of Certificate:

1. Products: products listed in Appendix 1 to the Guidelines or which have been evaluated by the Administration in accordance with 1.2.4 of the Guidelines should be listed. In respect of the latter “new” products, any special requirements provisionally prescribed should be noted.
2. Products: The list of products the vessel is suitable to carry should include the noxious liquid substances of category D which are not covered by the Guidelines and should be identified as “IBC Code Chapter 18 category D”.

**ENDORSEMENT FOR ANNUAL AND INTERMEDIATE SURVEYS**

THIS IS TO CERTIFY that at a survey required by 1.5 of the Guidelines for the Transport and Handling of Limited Amounts of Hazardous and Noxious Liquid Substances in Bulk in Offshore Support Vessels, the vessel was found to comply with the relevant provisions of the Guidelines.

Annual survey: Signed: .....  
(signature of duly authorised official)  
Place: .....  
Date: .....

(seal or stamp of the Authority, as appropriate).

Annual\*/Intermediate\* survey: Signed: .....  
(signature of duly authorised official)  
Place: .....  
Date: .....

(seal or stamp of the Authority, as appropriate).

Annual\*/Intermediate\* survey: Signed: .....  
(signature of duly authorised official)  
Place: .....  
Date: .....

(seal or stamp of the Authority, as appropriate).

Annual survey: Signed: .....  
(signature of duly authorised official)  
Place: .....  
Date: .....

(seal or stamp of the Authority, as appropriate).

---

\* Delete as appropriate.




ATTACHMENT 2 TO THE CERTIFICATE OF FITNESS

TANK PLAN (specimen)

Name of vessel: .....

Distinctive number or letters: .....



Date: .....  
(as for Certificate)

.....  
(signature of official issuing  
the Certificate and/or  
seal of issuing authority)

## TABLE OF CORRESPONDING REGULATIONS

In this table:

“*Cargo Ship Regulations*” means the Merchant Shipping (Cargo Ship Construction and Survey) Regulations 1984;\*  
 “*Fire Protection Regulations*” means the Merchant Shipping (Fire Protection) Regulations 1984; †  
 “*IBC Code Regulations*” means the Merchant Shipping (IBC Code) Regulations 1987; ‡  
 “*Gas Carriers Regulations*” means the Merchant Shipping (Gas Carriers) Regulations 1986; §  
 “*CPNLSB Regulations*” means the Merchant Shipping (Control of Pollution by Noxious Liquid Substances in Bulk) Regulations 1987. ¶

Column 1 Paragraph in Guidelines	Column 2 1974 SOLAS Regulations	Column 3 Corresponding UK Regulation
1.5.2	Regulation 10, Chapter VII Regulation 13, Chapter VII	Regulations of IBC Code Regulations Regulation 5 of Gas Carriers Regulations
3.6.2	II-2/59: 59.1 II-2/59: 59.2 II-2/59: 59.3	Regulation 12 of Cargo Ship Regulations Regulation 50 of Fire Protection Regulations Regulation 13 of Cargo Ship Regulations
3.8	II-1 Part D. Electrical Requirements	Part IV of Cargo Ship Regulations
3.9.1	II-2. Requirements for Tankers	Part 2B of Cargo Ship Regulations and Part IV Fire Protection Regulations
3.9.1.1 } 3.9.1.7 }	II-2/60, 61 and 62	Regulation 49 of Fire Protection Regulations
3.9.1.1 } 3.9.1.8 }	II-2/63	Regulation 51 of Fire Protection Regulations
3.9.1.2	II-2/56.1, 56.2, 56.4, 56.7, 56.8	Regulation 10 of Cargo Ship Regulations and Regulation 129 of Fire Protection Regulations
3.9.1.3	II-2/57.1 } II-2/42.5.1 }	Regulation 127 of Fire Protection Regulations
3.9.1.4	II-2/44 } II-2/58 }	Regulation 127 of Fire Protection Regulations
3.9.1.5	II-2/59	Regulation 50 of Fire Protection Regulations
3.9.1.6	II-2/4 II-2/7	Regulation 29 of Fire Protection Regulations Regulations 33, 34, 35 of Fire Protection Regulations
3.9.2.4	II-2/22	Regulation 144 of Fire Protection Regulations
3.9.2.5	II-2/5.1	Schedule 10(1) of Fire Protection Regulations
3.9.2.5	II-2/5.1.6	Schedule 10(1)(f) of Fire Protection Regulations
3.9.2.5	II-2/5.2	Schedule 10(2) of Fire Protection Regulations
3.9.2.5	II-2/5.3	Schedule 10(3) of Fire Protection Regulations
3.11	II-2/59.3	Regulation 13 of Cargo Ship Construction Regulations
5.2	II-2/17	Regulation 53 of Fire Protection Regulations

\* SI 1984/1217 as extended by SI 1985/661 and amended by SI 1986/1067.

† SI 1984/1218 as amended by SI 1985/1193 and SI 1986/1070..

‡ SI 1987/549 as amended by SI 1990/2602.

§ SI 1986/1073.

¶ SI 1987/551 as amended by SI 1990/2604.

Column 1 Paragraph in Guidelines	Column 2 MARPOL 73/78 Annex II Regulations	Column 3 Corresponding UK Regulation
1.5.2	Regulation 11	Regulation 24 of CPNLSB Regulations
4.1	Standards	Regulations 19 and 20 of CPNLSB Regulations
4.2	Construction and Equipment	Regulation 21 of CPNLSB Regulations